

**p1** 





## NATURAL EXPRESSION

Our passive flagship system will excite you like no other passive system has ever done.

## Timeless design

The unpretentious, well-proportioned, and ultra smooth design excited us when crafting the p1. And it's also true for the sound reproduction: no-frills, pure sound.

## **Perfect interaction**

A sealed cabinet with a woofer that is able to reproduce even the lowest octaves, a crossover which distributes energy adequately instead of wasting it are just some of the technical achievements within the p1.

## Leading the way

Our carefully handpicked state-of-the-art components and an enclosure that follows acoustical principles and supports the reproduction of sound will grant you direct access to more than crystal clear sound: experience the sheer power of all natural musical details embedded in sound! From the buzzing of a string, the hardly noticeable moan of the artist, the vibration of the sounding board, the slight scratching of the voice. Just like in reality

General	
Type	Passive 2-Way Floorstanding Speaker
Impedance	4 Ohms
Frequency range	40 Hz – 40 kHz
Crossover frequency	360 Hz
Maximum SPL	106 dB Peak
Dimensions (H $\times$ W $\times$ D)	44.8 × 10.6 × 8.4" (1139 × 270 × 214 mm)
Weight	61.7 lbs (28 kg)
Chassis	
HF	Manger® Sound Transducer, Bandwidth 80 Hz – 40 kHz, Rise Time 13 μs
LF	8" (200 mm) Custom made Carbon Fiber-Paper Sandwich Design,
	42 mm Voice Coil Diameter
Enclosure	closed
Various	
Recommended amplifier power	50 – 200 watts
Connectors	Bi-Wiring Terminal – WBT-Speakersockets nextgen™ Cu
SAM® Processing	available
Finish	silk matt as per RAL, Nextel, veneer or UltraHigh Gloss
Selection	
	100 A34
_	
RAL 7016 RAL 9017 RAL 1028 RAL 10	36 Cherry

your partner